



VERTIV™



PRASA®

Liebert™

GXT MT+
6/10/20 kVA



Liebert GXT MT+

6 kVA - 20 kVA 1x1 / 3x1 UPS System



FEATURES

- IGBT Based Rectifier
- True Online Double Conversion with DSP Control Technology for High Performance and Reliability.
- New Graphical LCD Display Provides UPS Data, Alarms and Helps in faults diagnostics and trouble shooting.
- Double Conversion Efficiency upto 90%.
- Active Input Power Factor Correction 0.99.
- 0.8 Output Power Factor.
- Wide Input Voltage window (110 - 280 Vac) for Indian Environmental Condition and for Optimized Battery Performance.
- Configurable Output Voltage (200/208/220/230/240 Vac.)
- Generator Compatible with Wide Input Frequency Range (40 Hz-70 Hz).
- 4 Stage Extendable Charging Design for optimized Battery Performance.
- Adjustable Battery Charging Current 1/2/4/6 Amps according to Battery Capacity and Rating.
- 50/60 Hz Automatic Frequency Converter Mode.
- Intelligent Monitoring with Standard RS232/USB Port Plus Slot Available for RS485/Dry Contact/SNMP Card.
- Inbuilt OVCD.

True Online Double Conversion UPS with optional built - in galvanic isolation & with extended runtime capabilities

Liebert GXT MT+ Series systems is true double conversion online UPS systems designed to provide with a capacity of 6/10/20 kVA. Liebert GXT MT+ units feature total isolation of the load from the mains - isolating input and output sections, and making the systems ideal for Data Networks / Small Data Centers/VOIP Applications application. The units support hot standby configuration, making them suited for critical applications like banks.



Liebert GXT-MT+ 6 & 20 kVA

Liebert GXT MT+

6 kVA - 20 kVA 1x1 / 3x1 UPS System



VERTIV™



MODEL		GXT MTX+ 06 kVA	GXT MT+ 06 kVA	GXT MT+ 10 kVA	GMT MT+ 10KVA	GMT MT+ 20KVA
PHASE		1 phase in / 1 phase out			3 phase in / 1 phase out	
CAPACITY		6000 VA/4800 Watt	6000 VA/4800 Watt	10000 VA/8000	10000 VA / 9000 W	20000 VA / 18000 W
INPUT Characteristics						
Nominal Voltage		230 Vac (1 Ph+ N)			3 x 400 VAC (3Ph+N)	
Voltage Range		160 Vac-300 Vac (1-phase) @ 100% load			305-478 VAC (3-phase) @ 100% load	
Frequency Range		46~54 Hz or 56~64Hz				
Power Factor		≥ 0.99 @ 100% load				
THDi		< 6% @ 100% load				
OUTPUT Characteristics						
Output Voltage		208 **/220/230/240VAC				
AC Voltage Regulation (Batt. Mode)		± 1%				
Frequency Range (Synchronized Range)		46~54Hz or 56~64Hz				
Frequency Range (Batt. Mode)		50 Hz ± 0.1 Hz or 60 Hz ± 0.1 Hz				
Current Crest Ratio		3:1 (max.)				
Harmonic Distortion		</=3% THD(Linear load), </=7% THD(Non linear load)	≤ 2 % THD (Linear Load) ; ≤ 5 % THD (Non-linear Load)			
Transfer Time	AC Mode to Batt. Mode			zero		
	Inverter to Bypass			zero		
Waveform (Batt. Mode)		Pure Sinewave				
AC Mode Efficiency		>84%	91%		>92%	>92%
ECO Mode Efficiency		97%				
BATTERY Characteristics						
Battery Type		SMF			SMF or Tubular	
Numbers		16-20*** (adjustable)			18-20**** (adjustable)	
Charging Current (max.)		6 Amps settable to 1/2/3/4/5/6 Amps			12A settable to 2/4/6/8/10/12 Amps	
Charging Voltage		273 VDC ± 1% (Based on 20pcs batteries)				
INDICATORS						
LCD Panel		UPS status, Load level, Battery level, Input/Output voltage, Discharge timer, and Fault conditions				
ALARM						
Battery Mode		Sounding every 4 seconds				
Low Battery		Sounding every second				
Overload		Sounding twice every second				
Fault		Continuously sounding				
PHYSICAL						
Dimension, D X W X H (mm)		369 X 190 X 630	369 x 190 x 318	442 x 190 x 318	592 X 250 X 576	592 x 250 x 826
Net Weight (kgs)		72	21	23	28	45
ENVIRONMENT						
Operation Humidity		0-95 % RH @ 0- 40°C (non-condensing)				
Noise Level		< 65 dB @ 1 meter	< 55 dB @ 1 meter		< 58dB @ 1 Meter	< 60dB @ 1 Meter
MANAGEMENT						
Smart RS-232/USB		Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7/8, Linux, Unix, and MAC				
Optional SNMP		Power management from SNMP manager and web browser				

* Product specifications are subject to change without further notice

**Derate capacity to 90% of capacity when the output voltage is adjusted to 208VAC

*** *When using batteries from 16-19, the unit will be de-rate according to formula ; P= Prating X N/20

**** *When using batteries from 18-19, the unit will be de-rate according to formula ; P= Prating X N/20



VERTIV™



PRASA®

Prasa Infocom & Power Solutions Pvt. Ltd.

🌐 www.prasa-pl.com ✉ enquiry@prasa-pl.com

VertivCo.com | E-mail : marketing.india@vertivco.com | Toll free : 1-800-2096070

Vertiv Energy Private Limited | Plot C-20, Rd No.19, Wagle Ind Estate, Thane (W), 400604. India

© 2016 Vertiv Co. All rights reserved.